DIGITAL AUDIO
IN
COAXIAL
OPTICAL
OUT
HDMI
IN
HDMI 4
HDMI 3
HDMI 2
HDMI 1
MONITOR OUT
OUT
COMPONENT VIDEO
IN
VIDEO 3
VIDEO 2
VIDEO 1
OUT
IN
S-VIDEO
VIDEO
MONITOR
VIDEO 5
OUT VIDEO 4 IN
OUT VIDEO 3 IN
VIDEO 2
VIDEO 1
ZONE 2
AUDIO
AUDIO 6
AUDIO 5
OUT AUDIO 4 IN
OUT AUDIO 3 IN
AUDIO 2
AUDIO 1
ZONE 2
7.1 CH INPUT
FRONT
SURR
SURR-B
CENTER
SUBW
AUDIO PRE-OUT
CAUTION :
SPEAKER IMPEDANCE
SPK A FRONT + SPK B :
8Ω MIN/SPEAKER
SPK A FRONT / SPK B :
4Ω MIN/SPEAKER
CENTER,
SURR,
SURR-BACK :
4Ω MIN/SPEAKER
XM
ANTENNA
FM
GND
AM
RS-232
SOFT CLIPPING
OFF ON
TRIGGER
OFF AUTO
IN
IR
OUT
+12V TRIGGER
FRONT
CENTER
SURROUND
SURR-BACK
SPEAKERS B
SPEAKERS A
NAD ELECTRONICS INTERNATIONAL
633 GRANITE COURT, PICKERING, ON CANADA L1W 3K1
MODEL T775 AV SURROUND SOUND RECEIVER
POWER RATING 120V ~ 60Hz 7A
DESIGNED & ENGINEERED IN CANADA, CUSTOM MANUFACTURED TO NAD SPECIFICATIONS IN CHINA
CAUTION
WARNING: SHOCK HAZARD - DO NOT OPEN
AVIS: RISQUE DE CHOC ELECTRIQUE - NE PAS OUVRIR
Manufactured under license from Dolby Laboratories. "Dolby, "Pro Logic", and the double-D symbol are trademarks of Dolby Laboratories
120V~60Hz
Serial No./No. De Series
SWITCHED
AC OUTLET 120V~60Hz
120W 1A MAX
POWER
ON
OFF
"HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC."